

**SDS**  
**Glass Frit, Lead Free**  
**GPP-22**



# Thompson Enamel

P.O. Box 310 Newport, KY 41072 USA ~ (859) 291-3800 fax (859) 291-1849

## **SECTION 1: Identification of the substance/mixture and of the company**

Product Name: Glass Painting Enamel, Lead Free

Identified uses: For enameling

Synonyms: Enamel, CX6449, Maroon

Supplier: Thompson Enamel

650 Colfax Avenue

Bellevue, Ky. 41073 U.S.A.

Phone: 859-291-3800

Fax: 859-291-1849

Email: info@thompsonenamel.com

## **SECTION 2: Hazards identification**

EEC Risk Phrases:

Not Evaluated

EEC Safety Phrases:

Not Evaluated

Methods for Cleanup:

See Section XI for Toxicological Information.

## **SECTION 3: Composition/Information on ingredients**

<u>Ingredients:</u>	<u>CAS No:</u>	<u>% Weight</u>	<u>EINECS</u>	<u>(Typical)</u>
Barium Sulfate	7727-43-7			0-2
Cl Pigment Red 108 (CdSeS)	58339-34-7*			5-10
Zinc-Boro-Silicate Glass Frit	65997-18-4* _____			70-80
Zinc-Boro-Silicate Glass Frit with cadmium	65997 -18-4*			0-10

Synonyms: CX6449 - Maroon Powder

<u>As Regulated</u> <u>(Related Exposure Limits)</u>	<u>OSHA PEL**</u> <u>(mg/m<sup>3</sup>)</u>	<u>OSHA PEL</u> <u>(mg/m<sup>3</sup>)</u>	<u>ACGIH TLV</u> <u>(mg/m<sup>3</sup>)</u>	<u>%Metal</u> <u>(Typical)</u>	<u>Sara</u> <u>313</u>
Barium Sulfate		5 Respirable	10 (Total particulate) 0.01, 0.002	0-2	No
Cadmium (as Cd) see 1910.1027		0.005	mg/m <sup>3</sup> Respirable	5-10	Yes
Fluorides (as F)		2.5	2.5	0-5	No
Glass- fused Particulates (Insoluble) Not Otherwise Regulated		5 Respirable, 15 mg/m <sup>3</sup> Total	3.0 Respirable, 10 mg/m <sup>3</sup> inhalable	70-90	No
Selenium compounds (as Se)	0.2	0.2	0.2	0-2	Yes
Silica -Quartz		10 /%SiO <sub>2</sub> +2 (Respirable)	0.05 Respirable	0-10	No

	Or			
	30/%SiO <sub>2</sub> +2			
	(Total dust)			
Zinc compounds (as Zn)	None		25-30	Yes
Zirconium compounds (as Zr)	5	5, 10 mg/m <sup>3</sup> STEL	0-5	No

\*\* The following PEL's were modified in 1989 but were challenged in 1992 and vacated. Several state programs may still recognize these.

#### **SECTION 4: First aid measures**

If inhaled:	If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.
On ingestion:	If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person. Call a physician.
On contact with eyes:	On contact with eyes flush eyes with plenty of water for at least fifteen (15) minutes. Call a physician.
On skin contact:	On skin contact, wash thoroughly with soap and water.

#### **SECTION 5: Firefighting measures**

Suitable extinguishing media:	This product will not burn. Use suitable extinguishing media for fighting surrounding fire.
Unsuitable extinguishing media:	Not applicable
Emitted when burned:	Not applicable
Special protective equipment:	This product will not burn. Use appropriate techniques for fighting surrounding fire.
Further information:	None

#### **SECTION 6: Accidental release measures**

Personal precautions:	Maintain appropriate dust control.
Environmental precautions:	Prevent contamination of soils, drains and surface water.
Methods for cleanup:	Transfer material into closed container for re-use or disposal.

#### **SECTION 7: Handling and storage**

Handling:	Good housekeeping procedures should be followed to prevent dust during processing. Do not eat, drink or smoke in work areas. Wash thoroughly with soap and water after handling. Provide eye wash stations in areas of handling.
Storage:	Store material in a closed container. Normal warehousing

#### **SECTION 8: Exposure Controls/Personal protection**

Engineering controls/measures:	Use mechanical ventilation to keep dust below regulatory standards (see Section II). Design criteria usually cannot be specified in an MSDS because of its complexity.
--------------------------------	--

Personal Protective Equipment:

Respiratory protection:

MSHA/NIOSH respirators approved for dusts TC-21C or NIOSH approved cartridges for Non-oil aerosols, N95, N99, N100 (42 CFR 84).

Hand protection:

Rubber, PVC coated gloves, impermeable.

Eye protection:

Safety Glasses with side shields, mono goggles.

Body protection:

No special precautions (see hand protection).

General safety and hygiene measures:

Good housekeeping procedures should be followed to prevent dust during processing.

## **SECTION 9: Physical and chemical properties**

Appearance:

Red Powder

Odor:

No Odor

Melting point/melting range:

Not Determined

Boiling point/boiling range:

Not applicable

Flash point:

Not applicable

Combustibility:

Not applicable

Explosion limits:

Lower Vol. %:

Not applicable

Upper Vol. %:

Not applicable

Ignition temperature:

Not applicable

Self-ignition:

Not applicable

Self-ignition temperature:

Not applicable

Explosion hazard:

Not applicable

Fire promoting properties:

Not applicable

Vapor pressure:

Not applicable

Specific gravity:

>1

Bulk density:

No data available

Packing density:

No data available

Solubility in Water:

<2

Solubility in other solvents:

Negligible

pH value:

No data available

Octanol/water partition coefficient (log POW):

Not applicable

Viscosity:

Not applicable

Other information:

Not applicable

## **SECTION 10: Stability and reactivity**

Conditions to avoid:

None known

Materials to avoid:

None known

Hazardous reactions:

None known

Hazardous decomposition products:

None known

## **SECTION 11: Toxicological information**

### Acute Toxicity

LD50/oral/rat:	Not Tested
LD50/inhal/rat:	Not Tested
Sensitizing:	None expected
Primary skin irritation/rabbit:	No data available
Primary mucous membrane irritation/rabbit' eyes:	No data available

### ADDITIONAL INFORMATION:

Zinc-Boro-Silicate or Zinc-Alkali-Boro- Silicate Glass Frit-

Repeated overexposure to this compound may cause eye, skin and respiratory tract irritation. Some compounds of the metals used in the manufacturing of this Frit, Zinc, have demonstrated various toxic properties (1,2,3,4).

However, there is no evidence that this frit has these toxic characteristics.

Long term overexposure to silica causes pneumoconiosis and silicosis, a form of pulmonary fibrosis. Continued exposure to silica can lead to cardiopulmonary impairment. Symptoms are usually delayed (10 years or more), but may appear in as little as 8-18 months after initial exposure.

Zinc is not inherently a toxic element. However, when heated, it evolves a fume of Zinc Oxide, when inhaled fresh, can cause a disease known as "Brass Chills" characterized by sweet taste, throat dryness, cough, weakness, generalized aching, fever, nausea, and vomiting. It is possible for people to become immune to it, but the immunity can be broken by cessation to exposure for a few days.

Routes of Entry:

Eyes: No    Skin: No    Inhalation: Yes    Ingestion: Yes

CARCINOGENICITY: NTP:                      Yes                      IARC Monographs:                      Yes

OSHA Regulated:                      No

Crystalline silica has been reviewed by IARC. IARC found limited evidence for carcinogenicity of crystalline silica in humans and sufficient evidence in experimental animals. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Monograph, Volume 68). Silica, crystalline is known to be a human carcinogen (NTP 10th Edition) Warning: This product contains a chemical known to the State of California to cause cancer.

Signs and Symptoms of Exposure:                      Irritation of the eyes, skin and respiratory tract.

Medical Conditions Generally Aggravated by Exposure:                      Respiratory and skin disorders aggravated by dust.

## **SECTION 12: Ecological information**

No specific ecological data available for this product.

## **SECTION 13: Disposal considerations**

Waste disposal recommendations: Trash can.

## **SECTION 14: Transportation information**

This product is not Department of Transportation (DOT) regulated.

This product is not TDG (Canada) regulated.

## **SECTION 15: Regulatory information**

Labeling according to EEC Directives: Not Evaluated

SARA

SARA 312:

Health:	Immediate (Acute):	No*	Fire:	None
	Delayed (Chronic):	Yes**	Reactivity:	None
			Sudden release of pressure:	None

\*Not an acute hazard, however may cause irritation due to abrasiveness.

\*\* See Section 11

SARA 313:

THIS PRODUCT CONTAINS A CHEMICAL OR CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372. THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

5-20% Cadmium Compound

5-10% Selenium Compound

70-90% Zinc Compound

Inventories

The ingredients of this product have been listed in the following inventories:

Europe EINECS:	Listed
U.S.A. TSCA:	Listed

HMIS Code:

## **SECTION 16: Other information**

References

DOT	Department of Transportation
OSHA	Occupational Safety and Health Administration
CAS	Chemical Abstracts Service
TSCA	Toxic Substances Control Act

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

The information and recommendations contained in this SDS have been compiled from sources believed to be reliable and to represent current opinion on the subject when the SDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

UPDATED MAY 2015